

1911 1912 1913 1914 1915 1916 1917 1918 1919 1920
 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930
 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940
 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950
 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960
 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970
 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980
 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990
 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000
 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010
 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020
 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030
 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040
 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050
 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060
 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070
 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080
 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090
 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100
 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110
 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120
 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130
 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140
 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150
 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160
 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170
 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180
 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190
 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200
 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210
 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220
 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230
 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240
 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250
 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260
 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270
 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280
 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290
 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300
 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310
 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320
 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330
 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340
 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350
 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360
 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370
 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380
 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390
 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400
 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410
 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420
 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430
 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440
 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450
 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460
 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470
 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480
 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490
 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500
 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510
 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520
 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530
 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540
 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550
 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560
 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570
 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580
 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590
 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600
 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610
 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620
 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630
 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640
 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650
 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660
 2661 2662 2663 2664 2665 2666 2667 2668 2

HYBRID ELECTRIC VEHICLE EMPLOYING PERMANENT
MAGNETIC TYPE DYNAMO-ELECTRIC MACHINE

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

The present invention relates to a hybrid electric vehicle employing a permanent magnetic type
5 dynamo-electric machine, and more particularly to a permanent magnetic type dynamo-electric machine structured such that a plurality of permanent magnets are inserted in a peripheral direction of a rotor, and a hybrid electric vehicle in which the dynamo-electric
10 machine and an engine are connected to a drive shaft in series and no switching gear between forward and backward movements is provided.

DESCRIPTION OF THE PRIOR ART

A power property of the vehicle is 1.05 to
15 1.2 times larger in a speed change ratio of a forward first speed than in a speed change ratio of a backward speed. This power property is required in an electric vehicle including a hybrid vehicle in the same manner, and a greatest torque should be output in the case of
20 backward movement.

In this case, in conventional, in order to intend to increase an output of a permanent magnet type dynamo-electric machine, there has been known a permanent magnet type dynamo-electric machine in which

a shape of magnets in a rotor is formed in nonsymmetrical at each pole and a motor-driven vehicle employing the same. As representative embodiments, there are Japanese Patent Unexamined Publication Nos. 8-33246, 5 9-182331 and 9-271151.

The structure described in Japanese Patent Unexamined Publication Nos. 8-33246 and 9-182331 is made such that in order to provide a permanent magnet type dynamo-electric machine suitable for one way 10 rotation, a punching hole for preventing a leakage flux is provided between the magnets, and a permanent magnet inserting hole is provided in an inner portion of an iron core in a rotor at a predetermined inclined angle with respect to a circumferential direction or a 15 permanent magnet is arranged so as to be shifted in a direction of rotation (normal rotation), thereby increasing a total amount of magnetic flux and utilizing a reluctance torque so as to increase an output.

Further, the structure described in Japanese 20 Patent Unexamined Publication No. 9-271151 is a permanent magnet type dynamo-electric machine for a motor-driven vehicle in which a magnet inserting hole is made long and a permanent magnet is arranged in a shifted manner, thereby increasing a torque. Further, 25 as a conventional embodiment of a permanent magnet type dynamo-electric machine for an electric vehicle, there is a structure described in Japanese Patent Unexamined Publication No. 9-261901. This technique corresponds

to a structure in which the arrangement of the permanent magnet is defined by a distance from a center of the rotor in order to intend to reduce the leakage flux.

5 In this case, among the conventional arts mentioned above, at first, in the former structure in which "the permanent magnets are nonsymmetrical at each pole", it is possible to increase the torque, however, it is intended to strengthen the magnetic flux in the
10 direction of rotation (normal rotation), so that the structure is applied to the dynamo-electric machine suitable for one way rotation. Further, the latter structure in which "the permanent magnets are nonsymmetrical at each pole" of course has the same power
15 property at both of the forward movement (normal rotation) and the backward movement (reverse rotation). Accordingly, it is unavoidable to be the dynamo-electric machine which can output 1.05 to 1.2 times the torque inherently required at the forward movement (the
20 same torque as that at the backward movement). Since an amount of magnetic flux is much together with outputting an unnecessary high torque, a weakening field current at a time of high speed rotation is increased so as to reduce an efficiency.

25 In particular, in a hybrid electric vehicle in which a permanent magnet type dynamo-electric machine and an engine are connected to a drive shaft in series and no gear for switching between forward and

backward movements is provided, since a torque of the engine is applied at a time of forward movement, it is not necessary that the forward torque is a high torque. Further, since the dynamo-electric machine and the engine are connected to the drive shaft in series, a rotational number of the dynamo-electric machine becomes the same as that of the engine, so that a specific fuel consumption is reduced unless a high efficiency is achieved at a time of high speed rotation.

On the contrary, at a time of backward movement, since the gear for switching between the forward and backward movements is not provided, a high torque corresponding to 1.05 to 1.2 times the forward movement is required only by the dynamo-electric machine. In this case, at a time of backward movement, since the engine and the dynamo-electric machine are disengaged by the clutch, a high speed rotation is not performed.

SUMMARY OF THE INVENTION

The present invention is made by taking the points mentioned above into consideration, and an object of the present invention is to provide a hybrid electric vehicle employing a permanent magnet type dynamo-electric machine structured such that a torque at a time of reverse rotation is greater than a maximum torque output by a dynamo-electric machine when the

dynamo-electric machine normally rotates.

Further, another object of the present invention is to provide a hybrid electric vehicle in which a dynamo-electric machine and an engine are
5 connected to a drive shaft in series and no gear for switching between forward and backward movements is provided, wherein there is employed a permanent magnet type dynamo-electric machine structured such that a torque output by the dynamo-electric machine when the
10 hybrid electric vehicle moves backward (the dynamo-electric machine reverse rotates) is greater than a maximum torque output by the dynamo-electric machine when the hybrid electric vehicle moves forward (the dynamo-electric machine normally rotates).

15 In order to achieve the object mentioned above, in accordance with the present invention, there is provided a hybrid electric vehicle employing the permanent magnet type dynamo-electric machine comprising:

20 a stator having a stator iron core around which a stator coil is wound; and

a rotor arranged in the stator at a rotational gap and having a plurality of permanent magnets arranged and fixed within a rotor iron core in a
25 peripheral direction,

wherein a ratio between a maximum torque output by the dynamo-electric machine when the dynamo-electric machine normally rotates and a torque output

by the dynamo-electric machine when reverse rotating establishes a relation $1 : 1.05-1.2$, whereby the torque at the reverse rotation becomes greater.

Further, in the permanent magnet type dynamo-
5 electric machine, the structure is preferably made such that a shape of the rotor at each pole is nonsymmetrical so that the ratio between the normal and reverse rotations establishes a relation $1 : 1.05-1.2$, whereby the torque at the reverse rotation becomes greater.

10 Further, in accordance with the present invention, the structure is preferably made such that a width in a rotational direction of a permanent magnet inserting hole provided within the rotor iron core is larger than a width of the permanent magnet, and a
15 space generated by a difference of length between the both is arranged in a normal rotation side of the dynamo-electric machine.

Further, in accordance with the present invention, the structure is preferably made such
20 that a rotor having no punching hole for preventing a leakage flux is provided, a permanent magnet inserting hole provided within the rotor iron core is provided at a predetermined inclined angle with respect to a circumferential direction so that a distance from the
25 rotational gap is greater in the normal rotation side of the dynamo-electric machine, and the permanent magnet is inserted to the inserting hole.

Further, in accordance with the present

invention, the structure is preferably made such that a cross sectional shape of the permanent magnet inserting hole and the permanent magnet is a rectangular shape.

Further, in accordance with the present
5 invention, the structure is preferably made such that a cross sectional shape of the permanent magnet inserting hole and the permanent magnet is an arc shape.

Further, in accordance with the present
invention, the structure is preferably made such that a
10 ratio between a width in a rotational direction of the permanent magnet inserting hole provided within the rotor iron core and a width of the permanent magnet is
1 : 0.5-0.9.

Further, in accordance with the present
15 invention, the structure is preferably made such that the permanent magnet inserting hole provided within the iron core forms a predetermined inclined angle $\theta = 10$ to 45 degrees (mechanical angle) with respect to a circumferential direction.

Further, in accordance with the present
20 invention, in order to achieve the object mentioned above, there is provided a hybrid electric vehicle having a dynamo-electric machine and an engine connected to a drive shaft in series and having no gear
25 for switching between forward and backward movements, wherein the dynamo-electric machine is a permanent magnet type dynamo-electric machine having each of the features mentioned above.

20250303 09:00:00

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a cross sectional view of a main portion of a permanent magnet type dynamo-electric machine in accordance with a first embodiment of the present invention;

Fig. 2 is a view showing a magnetic field analysis in the case that a relation $b/a = 0.85$ in Fig. 1 is established;

Fig. 3 is a view showing a magnetic flux density of a rotational gap between P1 and P2 in Fig. 2;

Fig. 4 is a view showing a forward movement torque and a backward movement torque in the case of changing the value b/a in Fig. 2;

Fig. 5 is a view showing a relation between a ratio between the forward and backward movement torque and the value b/a in Fig. 4;

Fig. 6 is a view showing an embodiment of a structure of a hybrid electric vehicle employing a permanent magnet type dynamo-electric machine in accordance with the present invention;

Fig. 7 is a view showing a difference of a torque curve between the present invention and the conventional embodiment;

Fig. 8 is a view showing a magnetic field analysis in the case of applying the present invention to an embodiment having sixteen poles ($b/a = 0.9$);

Fig. 9 is a view showing a relation between a

ratio between the forward and backward movement torque and the value b/a in the case of changing the value b/a in Fig. 8;

Fig. 10 is a cross sectional view of a main
5 portion of a permanent magnet type dynamo-electric machine in accordance with a second embodiment of the present invention;

Fig. 11 is a view showing a magnetic flux density of a rotational gap between P1 and P2 in Fig.

10 10; and

sup
Fig. 12 is a view showing a relation between the forward and backward movement torque and the value b/a in the case of changing θ in Fig. 10.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

15 A description will be given below of a first embodiment in which the present invention is applied to a permanent magnet type dynamo-electric machine having three phases, eight poles and forty eight slots with reference to Fig. 1 showing one pole pair. At first,
20 in Fig. 1, a stator 1 is the same as that of the conventional structure, and is constituted by inserting and arranging U-phase stator coils U1, V-phase stator coils V1 and W-phase stator coils W1 to forty eight slots 3 formed in an annular stator iron coil 2. An
25 opening portion 4 is formed in an inner peripheral portion of the stator iron core in correspondence to each of the slots.

Sub
B2

On the contrary, a rotor 6 is arranged in the stator 1 at a rotational gap and is structured such as to have auxiliary protruding poles in which a plurality of permanent magnets are arranged and fixed within a rotor iron core in a peripheral direction. That is, the rotor 6 is constituted by fitting and adhering a stator iron core 7 to a rotary shaft 9 and inserting and assembling a permanent magnet 8 having a width (b) in a rotational direction, for example, made of neodymium to a rectangular punching hole having a width (a) in the rotational direction and formed in a peripheral direction of an outer peripheral portion of the rotor iron core 7 from an axial direction so that N-pole and S-pole are alternately arranged in respective receiving portions. Further, the rotor 6 is rotatably arranged within the stator 1 in a state of having a predetermined rotational gap 5 with respect to an inner peripheral portion of the stator iron core 2. In this case, the rotor iron core 7 is constituted by laminating a multiplicity of silicon steel sheets on which holes for forming the receiving portions are formed.

In this case, the width (a) in the rotational direction of the punching hole is larger than the width (b) in the rotational direction of the permanent magnet, and the space 10 generated by a difference between the lengths (a) and (b) is arranged in a direction of normal rotation, that is, a direction of

forward movement of the hybrid electric vehicle. In this case, since the rotor becomes nonsymmetrical per each pole, the maximum torque becomes different in the case of normal rotation and reverse rotation, that is, the normal rotation having the space 10 has a low torque and the reverse rotation has a high torque. Further, a torque ratio between the normal rotation and the reverse rotation is determined by a ratio between the values a and b , and since both of the cases that a relation $b/a = 1$ is established (that is, the case that the punching hole and the magnet width are equal and the space 10 does not exist) and that a relation $b/a = 0$ is established (that is, the case that the magnet does not exist and only the space exists, so-called reluctance torque motor) are symmetrical at each pole, the torque of the normal rotation and the torque of the reverse rotation are equal to each other. On the contrary, since the case that a relation $b/a = 0.5$ is established (that is, the case that the width of the permanent magnet and the space 10 are equal) is most nonsymmetrical at each pole, the ratio between the torque of the normal rotation and the torque of the reverse rotation becomes maximum.

Fig. 2 shows a result of a magnetic field analysis in the case that the relation $b/a = 0.85$ is established in a dynamo-electric machine having an output 60 kW and Fig. 3 shows a distribution of a magnetic flux density of the rotational gap between P1

and P2 in the dynamo-electric machine in Fig. 2. In accordance with Fig. 3, since the magnetic flux density in the direction of normal rotation is low and the magnetic flux density in the direction of reverse rotation is high, it is known that the reverse rotation torque is larger than the normal rotation torque.

Further, Fig. 4 shows the forward movement torque and the backward movement torque in the case of changing the value b/a in the dynamo-electric machine shown in Fig. 2 and Fig. 5 shows a relation between a ratio between the forward and backward movement torque (the backward movement torque/forward movement torque) and the value b/a .

In accordance with Fig. 4, the torque is largest in the case that the relation $b/a = 1$ is established in both of the forward and backward movements, the torque is reduced as the value b/a becomes smaller, and the torque is smallest in the case that the relation $b/a = 0$ is established. However, in the case that the relation $b/a > 0.5$ is established, a reduction degree of the backward movement torque is smaller than that of the forward movement torque. In accordance with Fig. 5, it is known that the value b/a should be set to 0.5 to 0.9 in order to make the ratio between the forward and backward torque 1.05 to 1.2. If it is intended that the torque ratio is simply made 1.05 to 1.2, the value b/a 0.15 to 0.5 is sufficient, however, in this case, since the torque becomes too low

as is apparent from Fig. 4, the value is improper.

Sub 63
Here, Fig. 6 shows an embodiment of a structure of a hybrid electric vehicle corresponding to a subject of the present invention. A drive system is
5 mainly constituted by an engine 30, a motor 31 for driving an electric vehicle, a power generator 32 driven by the engine and used for charging a battery or the like, an inverter/converter 33, a battery 34, a drive shaft 37, a speed change gear (for example, a
10 CVT) 35, and a clutch 36. In this case, since the drive motor 31 functions as a power generator for regeneration at a time of reducing speed, the drive motor 31 may be sometimes called as a dynamo-electric machine. In this hybrid electric vehicle, the structure
15 is made such that the engine 30, the clutch 36, the dynamo-electric machine (driving motor) 31, the speed change gear 35 and the drive shaft 37 are connected to each other in series, and the speed change gear 35 does not have a gear for switching the front
20 and backward movements.

Operations in respective travel modes are as follows:

(1) Stop time: the engine is stopped, the clutch is turned off and the motor is in an idle state (in
25 this case, in the case that a charging amount of the battery is a little, the engine is driven so as to rotate the dynamo-electric machine as a power generator, thereby charging the battery).

(2) Low speed traveling time: the engine is stopped, the clutch is turned off and the motor is driven (in this case, in the case that the charging amount of the battery is a little, the engine is driven so as to rotate the power generator, thereby charging the battery).

mtz (3) Middle and high speed traveling time: the engine is driven, the clutch is turned on and the motor is rotates in an accompanying manner (no output).

10 (4) High speed accelerating time: the engine is driven, the clutch is turned on and the motor is driven.

July 85 (5) Speed reducing time: the engine is rotated due to inertia, the clutch is turned on and the motor is regenerated (may be regenerated by the power generator).


(6) Backward moving time: the engine is stopped, the clutch is turned off and the motor is driven (in this case, in the case that the charging amount of the battery is a little, the engine is driven so as to rotate the power generator, thereby charging the battery).

Since the backward movement is driven only by the motor, the motor torque at the backward moving time is large. On the contrary, the low speed travel is driven only by the motor, however, in the case that the torque is insufficient, the clutch is turned on so as to drive the engine, whereby it is easy to supplement

the insufficient torque.

Taking only the low speed side into consideration, the conventional motor having the relation $b/a = 1$ is sufficient, however, in the hybrid electric vehicle travel modes (3) and (4), the motor is driven or rotates in an accompanying manner even at the middle and high speed rotation time. In this case, when the magnetic flux of the magnet is great, an iron loss becomes great and a weakening field current is increased since the magnetic flux amount is restricted, so that a performance is reduced.

In accordance with the permanent magnet type dynamo-electric machine of the present invention, the torque in the backward movement side is secured, the insufficient torque at the low speed rotation time in the forward movement side is supplemented by an assistance of the engine, and the magnetic flux amount at the middle and high speed time is reduced, whereby it is possible to improve the performance such as an efficiency at the middle and high speed time or the like, and achieve a drive system suitable for the hybrid electric vehicle.

 Fig. 7 shows the motor torque in the case of the present invention ($b/a = 0.9$) and the conventional embodiment ($b/a = 1$). In accordance with this embodiment, the present invention can about 10% improve the rotational number in comparison with the conventional embodiment, and can about 1% improve the motor

B4 efficiency in the high speed side from 90% in the conventional one to 91% in the present invention.


In order to verify a wide use property of the present invention, the same verification is performed
5 in the dynamo-electric machine having an output 20 kW and 16 poles. Fig. 8 shows a result of a magnetic field analysis in the case that the relation $b/a = 0.9$ is established, and Fig. 9 shows a relation (in this case, between 0.5 and 1) between a ratio between the
10 forward and backward movement torque (backward movement torque/forward movement torque) and the value b/a in the case of changing the value b/a in the dynamo-electric machine in Fig. 8. In accordance with Fig. 9, it is known that the value b/a is between 0.5 and 0.9
15 in order to make the forward and backward movement torque ratio between 1.05 and 1.2 even in the structure having 16 poles.

Further, in the present invention, in order to change the torque of the forward and backward move-
20 ments, in addition to the method of partly forming the space as mentioned above, it is possible to achieve by the structure in which the permanent magnet inserting hole provided within the rotor iron core is provided at a predetermined inclined angle (θ) with respect to the
25 circumferential direction, and the dynamo-electric machine and the front movement (normal rotation) side of the hybrid electric vehicle employing the same are provided so that a distance from the rotational gap is

increased. In this case, the inclined angle (θ) means an inclined angle with respect to a tangent line in a center (in a rotational direction) of the permanent magnet.

5 Fig. 10 shows a result of magnetic field analysis in the case that a relation $\theta = 10$ degrees (mechanical angle) in a dynamo-electric machine having an output 60 kW and eight poles, and Fig. 11 shows a distribution of a magnetic flux density of a rotational
10 gap between P1 and P2 in the dynamo-electric machine in Fig. 10. As is apparent from Fig. 11, since the magnetic flux density in the direction of the normal rotation is low and the magnetic flux density in the direction of the reverse rotation is high, it is known
15 that the reverse rotation torque is larger than the normal rotation torque even in this case. In the case that the mechanical angle is 0 or 90 degrees, the torque ratio becomes 1 due to a symmetrical property at each pole. On the contrary, in the case of 45
20 degree, the torque ratio becomes greatest due to most nonsymmetrical property.

Fig. 12 shows the inclined angle (θ) and the ratio of the forward and backward movement torque. As is apparent from Fig. 12, when the angle θ is set to 10
25 to 45 degrees, it is possible to make the ratio of the forward and backward torque between 1.05 and 1.2.

 Further, in accordance with the present invention, the shape of the magnet is not limited to

the rectangular shape shown in the first embodiment, but can employ various shapes such as an arc shape or the like. Further, the permanent magnet 8 may employ the other magnets than the neodymium magnet, the number of (the number of the poles of) the permanent magnets may employ the other number than eight poles and sixteen poles, and the number of the slots of the stator may employ the other number than forty eight. In this case, the magnet is not limited to the inner rotation type and can be established by an outer rotation type.

In accordance with the present invention, since the ratio between the maximum torque output by the dynamo-electric machine at the normal rotation (forward movement) time and the torque output by the dynamo-electric machine at the reverse rotation (backward movement) time is 1 : 1.05 - 1.2 and becomes greater in the backward movement, it is possible to reduce the unnecessary torque (magnetic flux) at the normal rotation (forward movement) so as to improve the efficiency at the high speed and further improve the specific fuel consumption. Further, it is possible to provide the hybrid electric vehicle with compact, light and high efficiency which can output a predetermined torque at the backward movement.

Further, since it is possible to reduce the iron loss by reducing the magnetic flux at the high speed rotation, it is not necessary to use the low iron

5 to reduce the cost of the magnet.